




## ■ POT系列变压器 POT series transformer

### 结构及外形尺寸 Dimensions of structure and shape



Part Number	A (mm)	B (mm)	C (mm)	E (mm)	F (mm)	D (mm)	G (mm)	Pins(Optional)
GPOT30	32 max	39 max	15 max	5.0±0.5	37.5±0.5	3.0±0.5	0.6±0.1	5+5
GPOT30	32 max	35 max	15 max	5.0±0.3	31.0±0.5	3.5±0.5	0.6±0.1	5+5
GPOT30	32 max	30 max	12 max	5.0±0.5	/	3.0±0.5	0.8±0.1	5+0
GPOT30	32 max	33 max	26 max	5.0±0.5	27.5±0.5	3.5±0.5	0.8±0.1	5+5
GPOT33	36 max	39 max	22 max	5.0±0.5	33.5±0.5	3.5±0.5	0.8±0.1	5+5
GPOT33	36 max	39 max	28 max	5.0±0.5	33.5±0.5	3.5±0.5	0.8±0.1	5+5
GPOT40	43 max	45 max	28 max	5.0±0.5	39.5±0.5	3.5±0.5	0.8±0.1	5+6
GPOT40	43 max	45 max	28 max	5.0±0.5	/	3.5±0.5	0.8±0.1	5+0
GPOT40	43 max	47 max	22 max	5.0±0.5	/	3.5±0.5	0.8±0.1	6+0

### 特性 Features

POT系列变压器体积小、感抗高、绕线方便、磁屏蔽及散热效果均衡。

POT series transformer has small volume, high inductive reactance, convenient winding, balanced magnetic shielding and heat dissipation effect.

工作温度范围:-40~125°C

Operating temperature range:-40~125°C

### 应用 Applications

精密仪器

Precision instruments

程控交换机模块电源

The Stored program control exchange module power supply

医疗仪器电源,工业电源

Medical instrument power supply, industrial power supply

智能家用电器

Intelligent household appliances

★ 产品可以按客户要求定制

Products can be customized according to customer requirements